



TEST REPORT EN 62471:2008 Photobiological safety of lamps and lamp systems	
Report reference No	BST191214622002UR
Date of issue	2019-12-10
Testing laboratory	Shenzhen BST Technology Co., Ltd.
Address	Building No.23-24,Zhiheng Industrial Park,Guankouer Road,Nantou,Nanshan District,Shenzhen,Guangdong,China
Testing location	As above
Applicant1	SIGNCOMPLEX LIMITED
Address	Yijia Industrial Park, Fuqian Road, Guanlan Town, Bao' an, Shenzhen, Guangdong, China
Standard	EN 62471:2008
Test sample(s) received.....	2019-12-10
Test in period.....	2019-12-03 to 2019-12-10
Procedure deviation	N.A.
Non-standard test method	N.A.
This test report is for the customer shown above and their specific product only. It may not be duplicated or used in part without prior written consent from Shenzhen BST Technology Co., Ltd. (Shenzhen). This report must not be used by the customer to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the Federal Government.	
Type of test object	IP65 LINEAR HIGH BAY
Trademark	See page 4 of 17
Model/type reference	LHBP-300-AW-65K-ZYYY
Manufacturer.....	SIGNCOMPLEX LIMITED
Rating	See page 2 of 17



Label for LHBP-300-AW-65K-ZYYY (Representative):

IP65 LINEAR HIGH BAY
Model: LHBP-300-AW-65K-ZYYY
Rating(s):100-240V~, 50/60Hz, 3.5A, 300W



SIGNCOMPLEX LIMITED

Prepared by :

Paul Zhou

Engineer

Reviewer :

Yang yang

Supervisor

Approved & Authorized Signer :





Test item particulars

Tested lamp:Continuous wave lamps
Tested lamp system: According to lamp manufacture's recommendation
Lamp classification group.....: Exempt Group
Lamp cap: N.A.
Bulb.....: N.A.
Rated of the lamp:See page 2
Furthermore marking on the lamp.....: N.A.
Seasoning of lamps according EN standard: Seasoned for 24h before measurement
Used measurement instrument.....: NA
Temperature by measurement.....: 25°C
Information for safety use.....: N.A

Possible test case verdicts:

- test case does not apply to the test object.....:N(.A.)
- test object does meet the requirement.....P(ass)
- test object does not meet the requirement.....F(ail)

Germicidal remarks:

The test results presented in this report relate only to the object tested.
This report shall not be reproduced, except in full, without the written approval of the Issuing testing laboratory.
"(See Enclosure #)" refers to additional information appended to the report.
"(See appended table)" refers to a table appended to the report.
Throughout this report a point is used as the decimal separator.
List of test equipment must be kept on file and available for review.
This report consists of 15 pages and following appendices:
Appendix A EUT photos
Test environment:Temperature 25 degrees Celsius, dark room environment

Germicidal product information:

**1) Description of the product**

The products tested with model name listed below are LHBP-300-AW-65K-ZYYY provided in accordance with the requirements of EN 62471.

See total model list:

	Product name	Model number
Basic	IP65 LINEAR HIGH BAY	LHBP-300-AW-65K-ZYYY
Additional Model	IP65 LINEAR HIGH BAY	LHBP-300-AW-XXK-ZYYY, LHBP-280-AW-XXK-ZYYY, LHBP-240-AW-XXK-ZYYY, LHBP-200-AW-XXK-ZYYY, LHBP-180-AW-XXK-ZYYY, LHBP-150-AW-XXK-ZYYY, LHBP-120-AW-XXK-ZYYY, LHBP-100-AW-XXK-ZYYY, LHBP-080-AW-XXK-ZYYY, LHBP-070-AW-XXK-ZYYY, LHBP-050-AW-XXK-ZYYY XX: represents the color 27/30/35/40/45/50/57/60/65; YYY: can be any number or character for commercial use; Z: denotes control function, can be blank, D or S, blank denotes no dimmable or sensor control, "D" denotes 0-10/PWM Dimmable and "S" denotes sensor control.
Except for the model number and is different, the additional models are exactly same in shape of construction, material and electronic circuit with the basic model LHBP-300-AW-65K-ZYYY		

2) Factory information:

Factory: SIGNCOMPLEX LIMITED

Address: Yijia Industrial Park, Fuqian Road, Guanlan Town, Bao' an, Shenzhen, Guangdong, China

3) Manufacturer's name and trade-mark of identification mark:

Manufacturer's name : SIGNCOMPLEX LIMITED

Trade mark : 



EN 62471:2008			
Clause	Requirement + Test	Result - Remark	Verdict
4	<u>EXPOSURE LIMITS</u>		P
4.1	<u>Germicidal</u>		P
	The exposure limits in this standard is not less than 0,01 ms and not more than any 8-hour period and should be used as guides in the control of exposure	<u>Conform</u>	P
	Detailed spectral data of a light source are germicidally required only if the luminance of the source exceeds 104 cd.m^{-2}	<u>See clause 4.3</u>	P
4.3	<u>Hazard exposure limits</u>		P
4.3.1	<u>Actinic UV hazard exposure limit for the skin and eye</u>		P
	The exposure limit for effective radiant exposure is 30 J.m^{-2} within any 8-hour period	<u>Conform</u>	P
	To protect against injury of the eye or skin from ultraviolet radiation exposure produced by a broadband source, the effective integrated spectral irradiance, E_s , of the light source shall not exceed the levels defined by:		P
	$E_s \cdot t = \sum_{200-t}^{400} E_{\lambda}(\lambda, t) \cdot S_{UV}(\lambda) \cdot \Delta t \cdot \Delta \lambda \leq 30 \text{ J.m}^{-2}$		P
	The permissible time for exposure to ultraviolet radiation incident upon the unprotected eye or skin shall be computed by:		P
	$t_{\max} = 30 / E_s \geq 30000 \text{ s}$		P
4.3.2	<u>Near-UV hazard exposure limit for eye</u>		P
	For the spectral region 315 nm to 400 nm (UV-A) the total radiant exposure to the eye shall not exceed 10000 J.m^{-2} for exposure times less than 1000s. For exposure times greater than 1000 s (approximately 16 minutes) the UV-A irradiance for the unprotected eye, E_{UVA} , shall not exceed 10 W.m^{-2}		P
	The permissible time for exposure to ultraviolet radiation incident upon the unprotected eye for time less than 1000 s, shall be computed by:		P
	$t_{\max} \leq 10000 / E_{UVA} \text{ s}$		P
4.3.3	<u>Retinal blue light hazard exposure limit</u>		P
	To protect against retinal photochemical injury from chronic blue-light exposure, the integrated spectral radiance of the light source weighted against the blue-light hazard function, $B(_)$, i.e., the blue-light weighted radiance, LB , shall not exceed the levels defined by:		P



EN 62471:2008			
Clause	Requirement + Test	Result - Remark	Verdict
	$\underline{L_B \cdot t = \sum_{300}^{700} \sum L_{\lambda}(\lambda, t) \cdot B(\lambda) \cdot \Delta\lambda \leq 10^6 \text{ J} \cdot \text{m}^{-2} \cdot \text{sr}^{-1}}$		P
	$\underline{L_B = \sum_{300}^{700} L_{\lambda} \cdot B(\lambda) \cdot \Delta\lambda \leq 100 \text{ W} \cdot \text{m}^{-2} \cdot \text{sr}^{-1}}$		N
4.3.4	Retinal blue light hazard exposure limit - small source		N
	Thus the spectral irradiance at the eye E_{λ} , weighted against the blue-light hazard function $B(\lambda)$ shall not exceed the levels defined by: see table 4.2	See table 4.2	N
	$\underline{E_B \cdot t = \sum_{300}^{700} \sum E_{\lambda}(\lambda, t) \cdot B(\lambda) \cdot \Delta\lambda \leq 100 \text{ J} \cdot \text{m}^{-2}}$		N
	$\underline{E_B = \sum_{300}^{700} E_{\lambda} \cdot B(\lambda) \cdot \Delta\lambda \leq 1 \text{ W} \cdot \text{m}^{-2}}$		N
4.3.5	Retinal thermal hazard exposure limit		P
	To protect against retinal thermal injury, the integrated spectral radiance of the light source, L_{λ} , weighted by the burn hazard weighting function $R(\lambda)$ (from Figure 4.2 and Table 4.2), i.e., the burn hazard weighted radiance, shall not exceed the levels defined by:		P
	$\underline{L_R = \sum_{380}^{1400} L_{\lambda} \cdot R(\lambda) \cdot \Delta\lambda \leq \frac{50000}{\alpha \cdot t^{0.25}} \text{ W} \cdot \text{m}^{-2} \cdot \text{sr}^{-1}}$		P
4.3.6	Retinal thermal hazard exposure limit – weak visual stimulus		N
	For an infrared heat lamp or any near-infrared source where a weak visual stimulus is inadequate to activate the aversion response, the near infrared (780 nm to 1400 nm) radiance, LIR, as viewed by the eye for exposure times greater than 10 s shall be limited to:		N
	$\underline{L_{IR} = \sum_{780}^{1400} L_{\lambda} \cdot R(\lambda) \cdot \Delta\lambda \leq \frac{6000}{\alpha} \text{ W} \cdot \text{m}^{-2} \cdot \text{sr}^{-1}}$		N
4.3.7	Infrared radiation hazard exposure limits for the eye		P
	The avoid thermal injury of the cornea and possible delayed effects upon the lens of the eye (cataractogenesis), ocular exposure to infrared radiation, EIR, over the wavelength range 780 nm to 3000 nm, for times less than 1000 s, shall not exceed:		P



EN 62471:2008			
Clause	Requirement + Test	Result - Remark	Verdict
	$E_{IR} = \sum_{780}^{3000} E_{\lambda} \cdot \Delta\lambda \leq 18000 \cdot t^{-0,75} \quad W \cdot m^{-2}$		P
	For times greater than 1000 s the limit becomes:		N
	$E_{IR} = \sum_{780}^{3000} E_{\lambda} \cdot \Delta\lambda \leq 100 \quad W \cdot m^{-2}$		N
4.3.8	Thermal hazard exposure limit for the skin		N
	Visible and infrared radiant exposure (380 nm to 3000 nm) of the skin shall be limited to:		N
	$E_H \cdot t = \sum_{380}^{3000} \sum_t E_{\lambda}(\lambda, t) \cdot \Delta\lambda \leq 20000 \cdot t^{0,25} \quad J \cdot m^{-2}$		N
5	MEASUREMENT OF LAMPS AND LAMP SYSTEMS		P
5.1	Measurement conditions	Seasoned for 24h before measurement	P
	Measurement conditions shall be reported as part of the evaluation against the exposure limits and the assignment of risk classification.	See above	P
5.1.1	Lamp ageing (seasoning)	See above	P
	Seasoning of lamps shall be done as stated in the Appropriate EN lamp standard.	Under manufacture's recommendation	P
5.1.2	Test environment	Under manufacture's recommendation	P
	For specific test conditions, see the appropriate EN lamp standard or in absence of such standards, the appropriate national standards or manufacturer's recommendations.	Under manufacture's recommendation	P
5.1.3	Extraneous radiation	Considered	P
	Careful checks should be made to ensure that extraneous sources of radiation and reflections do not add significantly to the measurement results.	Considered	P
5.1.4	Lamp operation		N
	Operation of the test lamp shall be provided in accordance with:		N
	– the appropriate EN lamp standard, or		N
	– the manufacturer's recommendation		N
5.1.5	Lamp system operation		P
	The power source for operation of the test lamp shall be provided in accordance with:		P



EN 62471:2008			
Clause	Requirement + Test	Result - Remark	Verdict
	– the appropriate EN standard, or		N
	– the manufacturer' s recommendation		P
5.2	Measurement procedure		P
5.2.1	Irradiance measurements		P
	Minimum aperture diameter 7mm.		P
	Maximum aperture diameter 50 mm.		P
	The measurement shall be made in that position of the beam giving the maximum reading.		P
	The measurement instrument is adequate calibrated.		P
5.2.2	Radiance measurements		P
5.2.2.1	Standard method		P
	The measurements made with an optical system.		P
	The instrument shall be calibrated to read in absolute radiant power per unit receiving area and per unit solid angle to acceptance averaged over the field of view of the instrument.		P
5.2.2.2	Alternative method		N
	Alternatively to an imaging radiance set-up, an irradiance measurement set-up with a circular field stop placed at the source can be used to perform radiance measurements.		N
5.2.3	Measurement of source size		P
	The determination of α , the angle subtended by a source, requires the determination of the 50% emission points of the source.		P
5.2.4	Pulse width measurement for pulsed sources		N
	The determination of Δt , the nominal pulse duration of a source, requires the determination of the time during which the emission is > 50% of its peak value.		N
5.3	Analysis methods		P
5.3.1	Weighting curve interpolations		P
	To standardize interpolated values, use linear interpolation on the log of given values to obtain intermediate points at the wavelength intervals desired.	see table 4.1	P
5.3.2	Calculations		P
	The calculation of source hazard values shall be performed by weighting the spectral scan by the appropriate function and calculating the total weighted energy.		P
5.3.3	Measurement uncertainty		P



EN 62471:2008			
Clause	Requirement + Test	Result - Remark	Verdict
	The quality of all measurement results must be quantified by an analysis of the uncertainty.		P
6	LAMP CLASSIFICATION		P
	For the purposes of this standard it was decided that the values shall be reported as follows:	see table 6.1	P
	– for lamps intended for germicidal lighting service, the hazard values shall be reported as either irradiance or radiance values at a distance which produces an illuminance of 500 lux, but not at a distance less than 200 mm		P
	– for all other light sources, including pulsed lamp sources, the hazard values shall be reported at a distance of 200 mm		N
6.1	Continuous wave lamps		P
6.1.1	Exempt Group		P
	In the except group are lamps, which does not pose any photobiological hazard. The requirement is met by any lamp that does not pose:		P
	– an actinic ultraviolet hazard (ES) within 8-hours exposure (30000 s), nor		P
	– a near-UV hazard (EUVA) within 1000 s, (about 16 min), nor		P
	– a retinal blue-light hazard (LB) within 10000 s (about 2,8 h), nor		P
	– a retinal thermal hazard (LR) within 10 s, nor		P
	– an infrared radiation hazard for the eye (EIR) within 1000 s		P
6.1.2	Risk Group 1 (Low-Risk)	Exempt Group provided	N
	In this group are lamps, which exceeds the limits for the except group but that does not pose:		N
	– an actinic ultraviolet hazard (ES) within 10000 s, nor		N
	– a near ultraviolet hazard (EUVA) within 300 s, nor		N
	– a retinal blue-light hazard (LB) within 100 s, nor		N
	– a retinal thermal hazard (LR) within 10 s, nor		N
	– an infrared radiation hazard for the eye (EIR) within 100 s		N
	Lamps that emit infrared radiation without a strong visual stimulus and do not pose a near-infrared retinal hazard (LIR), within 100 s are in Risk Group 1.		N
6.1.3	Risk Group 2 (Moderate-Risk)	Exempt Group provided	N
	This requirement is met by any lamp that exceeds the limits for Risk Group 1, but that does not pose:		N
	– an actinic ultraviolet hazard (ES) within 1000 s exposure, nor		N



EN 62471:2008			
Clause	Requirement + Test	Result - Remark	Verdict
	– a near ultraviolet hazard (EUVA) within 100 s, nor		N
	– a retinal blue-light hazard (LB) within 0,25 s (aversion response), nor		N
	– a retinal thermal hazard (LR) within 0,25 s (aversion response), nor		N
	– an infrared radiation hazard for the eye (EIR) within 10 s		N
	Lamps that emit infrared radiation without a strong visual stimulus and do not pose a near-infrared retinal hazard (LIR), within 10 s are in Risk Group 2.		N
6.1.4	Risk Group 3 (High-Risk)	Exempt Group provided	N
	Lamps which exceed the limits for Risk Group 2 are in Group 3.		N
6.2	Pulsed lamps		N
	Pulse lamp criteria shall apply to a single pulse and to any group of pulses within 0,25 s.		N
	A pulsed lamp shall be evaluated at the highest nominal energy loading as specified by the manufacturer.		N
	The risk group determination of the lamp being tested shall be made as follows:		N
	– a lamp that exceeds the exposure limit shall be classified as belonging to Risk Group 3 (High-Risk)		N
	– for single pulsed lamps, a lamp whose weighted radiant exposure or weighted radiance does is below the EL shall be classified as belonging to the Exempt Group		N
	– for repetitively pulsed lamps, a lamp whose weighted radiant exposure or weighted radiance dose is below the EL, shall be evaluated using the continuous wave risk criteria discussed in clause 6.1, using time averaged values of the pulsed emission		N



EN 62471:2008			
Clause	Requirement + Test	Result - Remark	Verdict

Table 4.1		Spectral weighting function for assessing ultraviolet hazards for skin and eye		-
Wavelength λ , nm	UV hazard function $S_{UV}(\lambda)$	Wavelength λ , nm	UV hazard function $S_{UV}(\lambda)$	
200 0	0.032	313* 0	0.008	
205 0	0.013	315 0	0.005	
210 0	0.075	316 0	0.0023	
215 0	0.091	317 0	0.0021	
220 0	0.120	318 0	0.0010	
225 0	0.135	319 0	0.0018	
230 0	0.170	320 0	0.0010	
235 0	0.230	322 0	0.00061	
245 0	0.360	325 0	0.00055	
250 0	0.420	328 0	0.00046	
254* 0	0.550	330 0	0.00042	
255 0	0.580	333* 0	0.00037	
260 0	0.650	335 0	0.00034	
265 0	0.830	340 0	0.00028	
270 1	0.870	345 0	0.00024	
275 0	0.950	350 0	0.00020	
280* 0	0.880	355 0	0.00018	
285 0	0.770	360 0	0.00015	
290 0	0.640	365* 0	0.00011	
295 0	0.550	370 0	0.000093	
297* 0	0.480	375 0	0.000077	
300 0	0.300	380 0	0.000064	
303* 0	0.120	385 0	0.000053	
305 0	0.060	390 0	0.000044	
308 0	0.026	395 0	0.000036	
310 0	0.015	400 0	0.000030	

* Wavelengths chosen are representative: other values should be obtained by logarithmic interpolation at intermediate wavelengths.
 * Emission lines of a mercury discharge spectrum.



EN 62471:2008

Clause	Requirement + Test	Result - Remark	Verdict
--------	--------------------	-----------------	---------

Table 4.2		Spectral weighting functions for assessing retinal hazards from broadband optical sources		-
Wavelength nm	Blue-light hazard function B()	Burn hazard function R()		
300	0,01	-		
305	0,01	-		
310	0,01	-		
315	0,01	-		
320	0,01	-		
325	0,01	-		
330	0,01	-		
335	0,01	-		
340	0,01	-		
345	0,01	-		
350	0,01	-		
355	0,01	-		
360	0,01	-		
365	0,01	-		
370	0,01	-		
375	0,01	-		
380	0,01	0,1		
385	0,016	0,16		
390	0,020	0,20		
395	0,05	0,5		
400	0,10	1,0		
405	0,20	2,0		
410	0,40	4,0		
415	0,80	8,0		
420	0,90	9,0		
425	0,95	9,5		
430	0,98	9,8		
435	1,00	10,0		
440	1,00	10,0		
445	0,95	9,5		
450	0,93	9,3		
455	0,90	9,0		
460	0,80	8,0		
465	0,70	7,0		
470	0,62	6,2		
475	0,56	5,6		
480	0,45	4,5		
485	0,40	4,0		
490	0,22	2,2		
495	0,16	1,6		
500-600	$10^{[(450-\lambda)/50]}$	1,0		
600-700	0,001	1,0		
700-1050	0,013	$10^{[(700-\lambda)/500]}$		
1050-1150	0,025	0,2		
1150-1200	0,05	$0,2 \cdot 10^{0,02(1150-\lambda)}$		
1200-1400	0,10	0,02		



EN 62471:2008			
Clause	Requirement + Test	Result - Remark	Verdict

* 1 Wavelengths chosen are representative: other values should be obtained by logarithmic interpolation at intermediate wavelengths.
 * Emission lines of a mercury discharge spectrum.

Table 5.4					-
Summary of the ELs for the surface of the skin or cornea (irradiance based values)					
Hazard Name	Relevant equation	Wavelength Range nm	Exposure aperture rad(deg)	Limiting aperture rad(deg)	EL in items of constant irradiance $W.m^{-2}$
Actinic UV skin & eye	$E_S = E \cdot S(_)$	200 – 400	< 30000	1,4 (80)	30/t
Eye UV-A	$E_{UVA} = E \cdot$	315 – 400	1000 >1000	1,4 (80)	10000/t 10
Blue-light small source	$E_B = E \cdot B(_) \cdot$	300 – 700	100 >100	< 0,011	100/t 1,0
Eye IR	$E_{IR} = E \cdot$	780-3000	1000 >1000	1,4 (80)	$18000/t^{0.75}$ 100
Skin thermal	$E_H = E$	380-3000	<10	2 sr	$20000/t^{0.75}$

Table 5.5					
Summary of the ELs for the retina (radiance based values)					
Hazard Name	Relevant equation	Wavelength Range nm	Exposure duration Sec	Field of view radians	EL in terms of constant radiance $W.m^{-2}.sr^{-1}$
Blue light	$LB = L.B(_)$	300-700	0.25-10 10-100 100-10000 10000	0.011.(t/10) 0.011 0.0011.t 0.1	$10^6/t$ $10^6/t$ $10^6/t$ 100
Retinal thermal	$LR = L.R(_)$	380-1400	<0.25 0.25-10	0.0018 0.011.(t/10)	$50000/(.t^{0.25})$ $50000/(.t^{0.25})$
Retinal thermal(weak visual stimulus)	$LIR = L.R(_)$	780-1400	>10	0.011	6000/



EN 62471:2008			
Clause	Requirement + Test	Result - Remark	Verdict

Table 6.1 Emission limits for risk groups of continuous wave lamps									P
Risk	Action spectrum	Units	Symbol	Exempt		Low risk		Mod risk	
				Limit	Result	Limit	Result	Limit	Result
Actinic UV	Suv(λ)	W.m ⁻²	E _S	0.001	5.67e-05	-	-	-	-
Near UV		W.m ⁻²	E _{UVA}	0.33	3.18e-03	-	-	-	-
Blue light	B(λ)	W.m ⁻² .sr ⁻¹	L _B	100	5.03e+01	10000	--	40000 00	-
Blue light,small sourc	B(λ)	W.m ⁻²	E _B	0,01*	-	1.0	-	400	-
Retinal thermal	R(λ)	W.m ⁻² .sr ⁻¹	L _R	1.43e+04	3.05e+02	1.43e+04	-	2.17e+05	-
Retinal thermal, Weak visual stimulus**	R(λ)	W.m ⁻² .sr ⁻¹	L _{IR}	4.92e+05	0.00e+00	4.92e+05	-	4.92e+05	-
IR radiation Eye		W.m ⁻²	E _{IR}	100	0.00e+00	570	-	3200	-
a(mrad)	15.7								
RG	RG0								
* Small source defined as one with α < 0,011 radian. Averaging field of view at 10000 s is 0,1 radian.									
** Involves evaluation of non-GLS source									



EN 62471:2008			
Clause	Requirement + Test	Result - Remark	Verdict

Appendix A EUT photos




Photo 1 General appearance



Photo 2 General appearance



Photo 3 General appearance

###End of the report###